



WIRE LIST

C1	WHITE	C2
1	BLACK+DRAIN+SPIRAL	1
2	RED	2
3	GREEN	5
4	ORANGE	6
5	BLUE	3
6	BRAID	4
SHELL		SHELL

- NOTES:
- CABLE:UL 2725[(28AWG*1P+AB60%)*2+22AWG*2C]+MALAY+AEB65% CLEAR MYLAR +BRAID 65%] OD:4.5mm COLOR:CLEAR
 - TESTING:
 - 100%TEST OPEN,SHORT,MISWIRE
 - CONTACT RESISTANCE:2 ohms MAX
 - INSULATION RESISTANCE:50M ohms MIN
 - HI-POT:300VDC/1S
 - ALL MATERIAL ROHS COMPLIANT.
 - Specify Length as Suffix on Part Number in mm.
For Example:
1394-10638-1500 = 1500mm Long IEEE 1394 Cable.

2	PVC	20G	45P PVC CLEAR	
1	IEEE 1394 6P	2 SET	SHELL:NICKEL PLATED PIN:G/F	
NO.	DESCRIPTION	Q'TY:	P/N	REMARKS

TOLERANCE	
LINEAR	ANGLES
X.±	X°±
.X±0.25	.X°±
.XX±0.15	.XX°±
.XXX±0.05	.XXX°±

GENESIS TECHNOLOGY, INC.
3F 5Bld GeXia 1 nd Park Longhua Shenzhen China

APPD: _____ MAT'L: _____
 CHKD: _____ FINISH: _____
 DRWN: _____ Q'TY: _____

TITLE: IEEE 1394 6P TO 6P CABLE ASSY			
PART NO.		1394-10638-XXXX	
DWG NO.		SC-10638	
UNITS	SCALE	SHEET	REV
MM	NONE	1 OF 1	A

[A]	ISSUED	AXL	2/7/07'
REV	ECN NO.	NAME	DATE