



POSITION	A±0.20	B±0.20	C±0.38	D	E	F
15 Pin	16.90	25.00	30.80	2.29	0.25	0.89
26 Pin	25.25	33.30	39.20	2.29	0.51	0.64
44 Pin	38.95	47.05	53.05	2.29	0.51	0.64
62 Pin	55.40	63.50	69.40	2.41	0.58	0.62

MATERIAL:

INSULATOR : PBT+30% GLASS FIBER (UL 94V-0) .
 CONTACT : COPPER ALLOY
 CONTACT FINISH : GOLD OVER NICKEL
 SHELL : STEEL ,NICKEL PLATED
 BOARDLOCK : BRASS,TIN PLATED
 RIVETED INSERT : BRASS,NICKEL PLATED

SPECIFICATION:

CURRENT RATING : 2 AMP
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC FOR 1 MINUTE.
 INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.
 CONTACT RESISTANCE : 15mΩ MAX.
 OPERATING TEMPERATURE : -55°C ~ +105°C.

RoHS Compliant

Order Information :

DBHD - $\frac{15}{1} \frac{2}{2} \frac{X}{3} \frac{1}{4} \frac{B}{5} \frac{X}{6} \frac{X}{7}$

1. SERIES NUMBER	DBHD : HIGH DENSITY D-SUB 90° 8.89mm MOUNT
2. POSITION	15 26 44 62
3. CONTACT TYPE	2: MALE
4. CONTACT PLATING	1 : SELECTIVE GOLD 2 : SELECTIVE 15u" GOLD 3 : SELECTIVE 30u" GOLD
5. INSULATOR COLOR	1: BLACK 2: 661C BLUE
6. INSULATOR MATERIAL	B : PBT C : NYLON
7. MATING AND MOUNTING OPTIONS	0 : 4-40 THREADED RIVETED W/BOARDLOCK 1 : BOARDLOCK AND JACK SCREWS ASSEMBLED

TOLERANCE	
LINEAR	ANGLES
X.±	X'±
.X±0.25	.X'±
.XX±0.15	.XX'±
.XXX±0.05	.XXX'±



TITLE: HIGH DENSITY D-SUB CONNECTOR
 RIGHT ANGLE MALE FOOTPRINT 8.89MM

PART NO. DBHD-152X1BX

DWG NO. SC-20154

[A]	ISSUED	Kevin	03/05/07'	.XX±0.15	.XX'±	APPD:	MAT'L:	DWG NO.	UNITS	SCALE	SHEET	REV
REV	ECN NO.	NAME	DATE	.XXX±0.05	.XXX'±	DRWN: Kevin	FINISH:	Q'TY:	MM	NONE	1 OF 1	A