

NOTES:

1. MATERIALS:

INSULATOR: GLASS FIBER REINFORCED THERMOPLASTIC
UL 94V-0, COLOUR IN WHITE
NUMERAL CONTACT: PHOSPHOR BRONZE, GOLD PLATING ON
CONTACT.TIN PLATED ON TAIL 100u",OVER NICKEL PLATED 50u"
SIMULATION CONTACT: PHOSPHOR BRONZE, GOLD PLATING
OVER NICKEL
LEG: BRASS,Tin Plated
RIVET:BRASS,Nickel Plated
SHELL: SPCC 0.5T WITH NICKEL PLATING.

2. ELECTRICAL

VOLTAGE RATING: 40 VAC R.M.S.
CURRENT RATING: 3.0 AMP.
INSULATION RESISTANCE: 1000 MEGOHM MIN.
DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC (R.M.S.)
CONTACT RESISTANCE: 20 MILLI OHMS MAX.(INITIAL)

3. MECHANICAL PERFORMANCE:

MATING FORCES: 4.5kgf MAXIMUM
UNMATING FORCES: 1kgf MINIMUM,4kgf MAXIMUM
DURABILITY: 100 CYCLES MINIMUM

4. ENVIRONMENTAL

TEMPERATURE RANGE: -20 °C TO +85°C

C ORDER INFORMATION

D DVXR- 2X XX -D W X 3 T 1

① ② ③ ④⑤⑥⑦

1. CONNECTOR:

DVIR: DVI-I (DVI DIGITAL & ANALOG) R/A CONNECTOR
DVDR: DVI-D (DVI DIGITAL) R/A CONNECTOR

2. TYPE:

20: FEMALE, DIP, DUAL LINK, SCREW INSTALLED
21: FEMALE, DIP, DUAL LINK, WITHOUT SCREW
22: FEMALE, DIP, DUAL LINK, SCREW NOT INSTALLED

3. POSITIONS

25: 25 POSITIONS (24+1)
29: 29 POSITIONS (24+5)

4. INSULATOR MATERIAL

D: NYLON 66.

5. INSULATOR COLOR

W: WHTIE

6. CONTACT PLATING

1: GOLD FLASH
5: GOLD 15 u"
6: GOLD 30 u"

7. SHIELD PLATING

3: NICKEL PLATED

PART NO.	DVXR-2XXX-DWX3T1	SHEET	REVISION
DWG NO.	SC-10256	2 OF 2	SEE SHEET 1