



NOTES:

1. CABLE:[26AWG(7/0.16)+SPIRAL]TIN
 INSULATION:SR-PVC,OD=∅1.3±0.05mm,COLOR:YELLOW.
 UL1185 OR APPROVED EQUIV.
 JACKET: 80°C PVC,DD=∅3.0±0.20mm,COLOR:BLACK.
2. RCA PLUG MOLDING MATERIAL: PVC
 YELLOW FOR J1 AND J2,
3. TESTING:
 (1) 100% TEST OPEN,SHORT,MISWRE.
 (2) INSULATION RESISTANCE: 5 MEGAOHMS MIN.
 (3) CONDUCTOR RESISTANCE: 3 OHMS MAX.
 (4) HI-POT: 200V DC.
4. RoHS COMPLIANT.
5. Specify Length as Suffix on Part Number in mm.
 For Example:
 RCA-10358-1800 = 1800mm Long RCA Cable.

WIRE LIST

J1	TIP	YELLOW	TIP	J2
	SLEEVE	SPIRAL	SLEEVE	

3	OVERMOLD	1SET	
2	PREMOLD	1SET	
1	RCA PLUG NI PLATED	2PCS	
NO.	PART NAME	Q'TY	NOTE.

TOLERANCE	
LINEAR	ANGLES
X.±	X'.±
.X±0.25	.X'±
.XX±0.15	.XX'±
.XXX±0.05	.XXX'±

GENESIS TECHNOLOGY, INC
1015 GRANT STREET S.E. ATLANTA, GA 30315

APPD: _____ MAT'L: _____
 CHKD: _____ FINISH: _____
 DRWN: AXL Q'TY: _____

TITLE: RCA PLUG CABLE ASSY			
PART NO.		RCA-10358-X	
DWG NO.		SC-10358	
	UNITS	SCALE	SHEET
	MM	NONE	1 OF 1
			REV A

[A]	ISSUED	AXL	1/3/07'
REV	ECN NO.	NAME	DATE