



- NOTES:
1. THE APPLICABLE CONNECTOR JEIDA Ver4.1 AND PCMCIA STANDARD.
 2. TOLERANCE:
 UP TO 6 ±0.10
 OVER 6 TO 30 ±0.15
 OVER 30 TO 120 ±0.20

| | | | | |
|----|----------------------|-----|-----------------|---|
| 3 | GROUND/CARDBUS 68POS | 1 | PHOSPHOR BRONZE | Under plating: Nickel 40u" Min. Shield area: Au5u"(stripe) over Ni 50u" Min.(dimple stripe) Solder area: Sn120u" Min. |
| 2 | DICMF FEMALE CONTACT | 68 | PHOSPHOR BRONZE | Under plating: Nickel 40u" Min. Contact area: Au30u" min. Solder area: Sn120u" Min. |
| 1 | HOUSING | 1 | LCP RESIN | Color:Black UL 94V-0 |
| NO | DESCRIPTION | QTY | MATERIAL | Finish Remark |

| TOLERANCE | |
|-------------|---------|
| LINEAR | ANGLES |
| X. ± | X° ± |
| .X ± 0.25 | .X° ± |
| .XX ± 0.15 | .XX° ± |
| .XXX ± 0.05 | .XXX° ± |



TITLE: 68P CARD BUS CONNECTOR
 PART NO. SC-10436

| | | | | | | | | | | | | |
|-----|--|------|----------|-------------|---------|-----------|---------|---------|-------|-------|--------|-----|
| REV | ECN NO. | NAME | DATE | .XXX ± 0.05 | .XXX° ± | DRWN: AXL | Q'TY: | DWG NO. | UNITS | SCALE | SHEET | REV |
| [B] | REVISE DIM. WAS 1.35 AND ADD TOLERANCE | AXL | 12/7/06' | .X ± 0.25 | .X° ± | APPD: | MAT'L: | DWG NO. | MM | NONE | 1 OF 1 | B |
| [A] | ISSUED | AXL | 8/7/06' | .XX ± 0.15 | .XX° ± | CHKD: | FINISH: | | | | | |