



NOTES:

1. CABLE: [28AWGx1P+24AWGx2C+A,E,B]TIN
 INSULATION: 1P: HD-PE, OD: $\phi 0.84 \pm 0.05$ mm, COLOR: WHITE, GREEN.
 2C: SR-PVC, OD: $\phi 1.05 \pm 0.05$ mm, COLOR: BLACK, RED.
 JACKET: PVC, OD: $\phi 4.7 \pm 0.1$ mm, COLOR: BLACK.UL2725.
2. 100% TEST: OPEN, SHORT AND MISWIRE.
3. INSULATION RESISTANCE: 20M ohms.
4. CONDUCTOR RESISTANCE: 5 ohms.
5. HI-POT: 200V DC.
6. ORDER INFORMATION OPTION [C]
 SC-10270-XX

- 01: LENGTH = 152.4 ± 15 mm
 02: LENGTH = 406.0 ± 20 mm

WIRE LIST

C1	COLOR	C2
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
5	DRAIN	SHELL

9	NUT	2PCS	NUT 4-40 UNC NI	
8	H.S.T	1PCS	HST OD=1.0 ,L=45MM,BLK	
7	H.S.T	1PCS	HST OD=5.0 ,L=25MM,BLK	
6	OVER-MOLD	30G	PVC: 45P BLACK	
5	INNER-MOLD	10G	PE, COLOR: CLEAR	
4	USB A/ F	1SET	G/F WHITE	
3	CABLE	1PCS	UL2725 28AWG*1P+ 24AWG*2C+AEB BLACK	
2	TERMINAL	5PCS	2.0MM PITCH TERM	2015T-LF-T120 (ALEX)
1	HOUSING	1PC	2.0MM PITCH HSG	2016-5 (ALEX)
NO.	DESCRIPTION	Q'TY	MATERIAL	P/N

				TOLERANCE		 <small>1015 GRANT STREET S.E. ATLANTA, GA 30315</small>		TITLE: USB A FEMALE PANEL MOUNT				
				LINEAR	ANGLES			PART NO.	SC-10270-XX [C]			
[C]	ADDED P/N LENGTH OPTION	Charlie	2/4/10'	X.±	X'.±	APPD:	MAT'L:	DWG NO.	SC-10270			
[B]	REVISED DRAWING	AXL	3/2/06'	.X±0.25	.X'±	CHKD:	FINISH:		UNITS	SCALE	SHEET	REV
[A]	ISSUED	AXL	2/28/06'	.XX±0.15	.XX'±	DRWN: AXL	Q'TY:		MM	NONE	1 OF 1	C
REV	ECN NO.	NAME	DATE	.XXX±0.05	.XXX'±							